

MAX CYLINDER HEAD
1350 x 395
MASS. TESTATA MOTORE



VOIGT - Werkzeugmaschinen
www.voigt-werkzeugmaschinen.de

SG 1400M



PTR 1600



HBM 810



HYDRAULIC VALVE GUIDE PRESS
EXTRACCIÓN E INSERTADO HIDRÁULICO DE GUÍAS DE VÁLVULA
PRESSA IDRAULICA PER GUIDA VALVOLE



For easy, safe and fast valve guide replacement. Reduces operator fatigue and costly operator error. The bench is equipped with a hydraulic cylinder for operation also on engine valves assembly and disassembling. Standard equipment includes tools for valve guide replacement (dismounting pilots), standard set of installation tools, and set of different size of compressing foot for any application.

SPECIFICATIONS

Horizontal Movement	mm	1100
Vertical Movement	mm	150
Upper Piston Movement	mm	150
Lower Piston Movement	mm	120
Table Rotation		50°
Working Pressure	bar	200
Adjustable Pressure	bar	0-250
Pressforce	Ton	0-16
Motor Power	kW	0,75
Rod Speed		28 mm/min
Tank Capacity	l	7
Electric voltage		400V, 3pH, 50Hz
Control voltage		24V

DIMENSIONS

Width	mm	1550
Depth	mm	900
Height	mm	1980
Weight	kg	380

Specifications subject to change without notice.

VOIGT - Werkzeugmaschinen
www.voigt-werkzeugmaschinen.de



CARMEC d.o.o.
Miren 227A
5291 Miren
SLOVENIA



t +386 5 305 44 68
m + 386 41 636 651
f +386 5 395 40 78
info@carmec.si

AUTOMOTIVE MACHINE TOOLS



www.carmec.si

